Drop-in anchor J+

Cross references

Setting tool
Cordless hammer drill

Application range

> Suspension systems
> Pipelines
> Air ducts
> Sprinkler systems
> Cable racks
> Machinery
> Consoles
> Ceiling girders

Properties

> Zinc-plated steel
> ETA-approved drop-in anchor, ideal for suspension systems
> Drop-in anchorxfor pre-installing with an assembly tool
> Internal thread for metric screws and rods
> The small required drill hole depth facilitates drilling and over-head mounting
> Suitable for sprinkler systems
> For dry indoor use

Base materials

Approved for
> Cracked concrete
> Non-cracked concrete

Applications

Technical specifications

Certifications





Order description	Internal thread [mm]	L [mm]	d_0 [mm]	h_1 [mm]	f_{max} [mm]	f_{min} [mm]	d_f [mm]	T_{inst} [Nm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
J+ 6	M6	25	8	27	10	6	7	4	100		9650070100	4061245093437
J+ 8	M8	30	10	33	13	8	9	11	100		9650070101	4061245093444
J+ 10	M10	40	12	43	17	10	12	17	50		9650070102	4061245093451
J+ 12	M12	50	15	54	21	12	14	38	25		9650070103	4061245093468
J+ 16	M16	65	20	70	27	16	18	60	10		9650070104	4061245093475
J+ 20	M20	80	25	86	34	20	22	100	5		9650070105	4061245093482

f_{max} = maximum installation depth; f_{min} = minimum installation depth; d_f = drill hole diameter in the attachment; T_{inst} = tightening torque; N_{Rec} = recommended tensile capacity; V_{Rec} = recommended shear load capacity; L = length; d_0 = diameter; h_1 = drill hole depth

EJOT SE & Co. KG · Market Unit Construction · In der Stockwiese 35 · 57334 Bad Laasphe · Germany
T +49 2752 908-0 · F +49 2752 908-731 · construction@ejot.com · www.ejot.com/construction