

Drop-in anchor JE+



Cross references

Setting tool
Cordless hammer drill

Application range

- > Suspension systems
- > Pipelines
- > Air ducts
- > Sprinkler systems
- > Cable racks
- > Machinery
- > Consoles
- > Ceiling girders

Properties

- > A4 stainless steel
- > ETA-approved drop-in anchor, ideal for suspension systems
- > Drop-in anchor for pre-installing with an assembly tool
- > Internal thread for metric screws and rods
- > The small required drill hole depth facilitates drilling and over-head mounting
- > Suitable for sprinkler systems
- > For dry indoor and outdoor areas

Base materials

- Approved for
- > Cracked concrete
 - > Non-cracked concrete



Applications



Technical specifications



Certifications



Order description	Internal thread [mm]	L [mm]	d ₀ [mm]	h ₁ [mm]	f _{max} [mm]	f _{min} [mm]	d _i [mm]	T _{inst} [Nm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JE+ 6	M6	25	8	27	10	6	7	4	100		9650070113	4061245093567
JE+ 8	M8	30	10	33	13	8	9	11	100		9650070114	4061245093574
JE+ 10	M10	40	12	43	17	10	12	17	50		9650070115	4061245093581
JE+ 12	M12	50	15	54	21	12	14	38	25		9650070116	4061245093598
JE+ 16	M16	65	20	70	27	16	18	60	10		9650070117	4061245093604
JE+ 20	M20	80	25	86	34	20	22	100	5		9650070118	4061245093611

f_{max} = maximum installation depth; f_{min} = minimum installation depth; d_i = drill hole diameter in the attachment; T_{inst} = tightening torque; N_{Rec} = recommended tensile capacity; V_{Rec} = recommended shear load capacity; L = length; d₀ = diameter; h₁ = drill hole depth