

Self-drilling screw JT2-ST-2-6.0 EJOGUARD




Application range

- > Fastening timber components to thin-walled steel substructures
- > Fastening of edge planks
- > To fix roofing membranes and insulating material to substructures made of sheet steel $\geq 0.70 \text{ mm} \leq 1.5 \text{ mm}$, timber or wood-based material in combination with EJOT stress plates


Properties

- > Case-hardened steel
- > EJOGUARD corrosion protection
- > With countersunk head

Applications




Technical specifications



Cross references

Bit hexalobular TX25
 Bit holder
 Cordless screwdriver ASCS 6.3
 Falt roof profile FP
 Stress plate EcoTek 50
 Stress plate EcoTek T 50
 Stress plate HTV82/40F
 Stress plate HTV 40 RU

Certifications



Product online



Order description	Length [mm]	Thread length [mm]	Clamping thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JT2-ST-2-6.0x40 EJOGUARD	40	40	0–27	500		7282110609	4061245014517
JT2-ST-2-6.0x60 EJOGUARD	60	45	15–47	500		7282119609	4061245014432
JT2-ST-2-6.0x80 EJOGUARD	80	65	15–67	250		7282112609	4061245014500
JT2-ST-2-6.0x100 EJOGUARD	100	65	35–87	250		7282113609	4061245014494
JT2-ST-2-6.0x120 EJOGUARD	120	65	55–107	250		7282114609	4061245014487
JT2-ST-2-6.0x140 EJOGUARD	140	65	75–127	250		7282115609	4061245014470

Further lengths available upon request

