

NEW T-FAST® wood screw JW4 wafer head



Application range

- > Fastening of non-pre-drilled or pre-drilled components made of wood, wood-based material and pre-drilled and pre-set steel components to non-pre-drilled or pre-drilled components made of solid wood, solid structural timber (KVH), glued-laminated timber (BSH), solid wood panels, laminated veneer lumber (LVL), wood-based panels or cross-laminated timber
- > For weathered areas
- > Suitable for universal application

Characteristics


- > Stainless steel CRC II or stainless steel A2 with dry lubricant
- > Wafer head (STS) for strong tightening during installation and increased holding forces after installation
- > Full and partial thread
- > Optimised thread geometry for improved prevention of screw over-tightening with short screws and accelerated processing with long screws
- > T-FAST® Plus point geometry facilitates the screwing-in process through quick point biting, low screwing-in torque and efficiently reduced wood splitting

Cross references


Cordless screwdriver ASCS QSW
Bit hexalobular TX



Applications



Technical specifications



Certifications



Product online



| Order description | d [mm] | l [mm] | l _g [mm] | d _h [mm] | Drive | PU [pieces] | Price/100 [EUR] | Article number | EAN |
|---------------------------------------|--------|--------|---------------------|---------------------|-------|-------------|-----------------|----------------|---------------|
| d 6.0 – full-threaded screw | | | | | | | | | |
| JW4-2-Plus-STS-6.0x40/35 S TX30 | 6.0 | 40 | 35 | 14.0 | TX30 | 100 | | 3820000483 | 4061245123905 |
| JW4-2-Plus-STS-6.0x60/52 S TX30 | 6.0 | 60 | 52 | 14.0 | TX30 | 100 | | 3820000484 | 4061245123912 |
| JW4-2-Plus-STS-6.0x80/70 S TX30 | 6.0 | 80 | 70 | 14.0 | TX30 | 100 | | 3820000485 | 4061245123929 |
| d 6.0 – partial threaded screw | | | | | | | | | |
| JW4-2-Plus-STS-6.0x100/80 S TX30 | 6.0 | 100 | 80 | 14.0 | TX30 | 100 | | 3820000486 | 4061245123936 |
| d 8.0 – full-threaded screw | | | | | | | | | |
| JW4-2-Plus-STS-8.0x60/50 M TX40 | 8.0 | 60 | 50 | 21.0 | TX40 | 50 | | 3820000487 | 4061245123943 |
| JW4-2-Plus-STS-8.0x80/70 M TX40 | 8.0 | 70 | 70 | 21.0 | TX40 | 50 | | 3820000440 | 4061245123950 |
| d 8.0 – partial threaded screw | | | | | | | | | |
| JW4-2-Plus-STS-8.0x100/80 M TX40 | 8.0 | 100 | 80 | 21.0 | TX40 | 50 | | 3820000446 | 4061245123967 |
| JW4-2-Plus-STS-8.0x120/80 M TX40 | 8.0 | 120 | 80 | 21.0 | TX40 | 50 | | 3820000455 | 4061245123974 |