

TP300



Application range

This joint sealing tape is suitable for joint constructions such as window couplings, concealed window connection joints or as a sealant border.

TP300 can also be used as filling tape - especially in metal construction. In this function it realises windproof and heat insulating properties. Corresponds to type 2 according to IFBS data sheet and BG 2.

Properties

- > Open-cell flexible polyurethane foam impregnated with flame-retardant synthetic resin
- > TP300 is manufactured without halogen-containing flame retardants, solvent-free and without using HCFCs/CFCs/CFCs
- > TP300 is supplied as compressed roll material, with one-sided self-adhesion in grey

Note

Do not expose the tape to direct sunlight permanently. The tape can be plastered / painted over. Illbruck silicone, acrylate and hybrid-based sealants are compatible with the tape. Further compatibilities can be requested from us. Sealing tape must be stored in a dry place until installation.

Technical specifications



Product online



Order description	Band width* [mm]	Application range [mm]	Roll length total [m]	Content roll [pieces]	PU [m]	Price/100 m [EUR]	Article number	EAN
TP 300 10 / 1-2 grey	10	1-2	25.00	11	275.0		0030010102	4025109294095
TP 300 10 / 2-3 grey	10	2-3	18.0	11	198.0		0030010203	4025109294200
TP 300 10 / 3-6 grey	10	3-6	13.0	11	143.0		0030010306	4025109294316
TP 300 15 / 1-2 grey	15	1-2	25.0	7	175.0		0030015102	4025109294101
TP 300 15 / 2-3 grey	15	2-3	18.0	7	126.0		0030015203	4025109294217
TP 300 15 / 3-6 grey	15	3-6	13.0	7	91.0		0030015306	4025109294323
TP 300 15 / 5-9 grey	15	5-9	7.0	7	49.0		0030015509	4025109294545
TP 300 15 / 6-12 grey	15	6-12	5.5	7	38.5		0030015612	4025109294644
TP 300 20 / 5-9 grey	20	5-9	7.0	5	35.0		0030020509	4025109294552
TP 300 20 / 6-12 grey	20	6-12	5.5	5	27.5		0030020612	4025109294651

*Dimensional tolerances according to DIN7715 P3